FIG. 1A.

HUB 10

LAN SWITCH 34

POWER SUPPLY 32

COMBINER 36

30

DATA

DATA+BACKUP POWER

DATA+POWER

DATA ONLY

SPARE PAIR
NO DATA NO POWER

DATA+POWER

DATA+POWER

18

22

20

16

DATA+BACKUP POWER

DATA+POWER

11

DATA+BACKUP POWER

12

HUB CAMERA 14

FIG. 1B

FIG. 2A

FIG. 2B

HUB 150

LAN SWITCH

POWER SUPPLY 182

POWER SUPPLY INTERFACE

180

186

184

DATA

172

170

199 CON

168

198 CON

DATA+BACKUP POWER

POWER

SPARE PAIR

DATA

DATA

151

DATA+POWER

151

166

196 CON

DATA+BACKUP POWER

DATA+BACKUP POWER

192 CON

DATA+POWER

162

194 CON

HUB CAMERA 164

FIG. 3A

FIG. 3B

FIG. 4A

FIG. 4B

FIG. 5

FIG. 6

SPARE DATA DATA+POWER DATA+POWER DATA+POWER

SEPARATOR 508

DATA

POWER

MAINS

POWER SUPPLY 504

DATA TRANSCEIVER 502

OTHER ELEMENTS 506

POWER SUPPLY 510

500

FIG. 7A

SPARE DATA DATA POWER

CONNECTOR 558

POWER

DATA

POWER SUPPLY 554

MAINS

DATA TRANSCEIVER 552

POWER SUPPLY 560

OTHER ELEMENTS 556

550

FIG. 7B

FIG. 8A

FIG. 8B

DATA

DATA

620

630

632

634

630

636

640

640

+V

TO / FROM FILTER

−V

+V

TO / FROM FILTER

−V

+V

−V

+V

−V

DATA +POWER CHANNEL

DATA +POWER CHANNEL

DATA +POWER CHANNEL

Rx OR Tx
TWISTED PAIR

DATA IN

C

660

C

DATA + POWER
OUT

650

FIG. 8C

+

−

DC POWER IN
FROM FILTER

FIG. 8D

680

C

C

+

Rx DATA IN

+

POWER + DATA OUT

690

C

C

−

−

Tx DATA IN

670

−

−

+

+

DC IN
FROM FILTER

FIG. 8E

POWER + DATA OUT

Rx DATA IN

Tx DATA IN

710

710

700

706

SENSING & CONTROL

SENSEING& CONTROL

708

702

704

ACTIVE FILTER

ACTIVE FILTER

ACTIVE FILTER

ACTIVE FILTER

+

+

−

−

+

−

DC IN

V_{REF}

706

702

702

+V
TO/FROM
FILTER

FIG. 8F

V_{REF}

708

$-V$
TO/FROM
FILTER

704

704

FIG. 8G

FIG. 9A

POWER &
Rx DATA

POWER &
Tx DATA

DC
OUTPUT

142

1610

1600

Rx DATA

Tx DATA

FIG. 9B

142

POWER & Rx DATA

POWER & Tx DATA

DC OUTPUT

DC OUTPUT

1636

1620

1630

1640

1634

1640

1632

1630

1630

Rx DATA

Tx DATA

1650

1660

Rx OR Tx

C

DATA & POWER IN

DATA OUT

C

FIG. 9C

+   −

DC POWER OUT

FIG. 9D

1670

Rx DATA & POWER IN

Tx DATA & POWER IN

1680

1690

C   C

C   C

Rx DATA OUT

Tx DATA OUT

+   +   −   −

DC POWER OUT

FIG. 9E

Rx DATA OUT

Tx DATA OUT

1710

1710

1700

1702

+

+

SENSE &
CONTROL

ACTIVE
FILTER

1706

ACTIVE
FILTER

1708

SENSE &
CONTROL

ACTIVE
FILTER

1704

ACTIVE
FILTER

+

DC POWER OUT

−

−

−

Rx DATA & POWER IN

Tx DATA & POWER IN

DATA+POWER

+DC
OUTPUT

V_{REF}

1706

1702

1702

FIG. 9F

DATA+POWER

−DC
OUTPUT

V_{REF}

−V

−V

1708

1704

1704

FIG. 9G

FIG. 10A

MANAGEMENT STATION 2040

2022

2020

2018

2016

2014 HUB CAMERA

2012

HUB 2010

LAN/WAN 2038

POWER MANAGEMENT & CONTROL UNIT

POWER SUPPLY 2032

LAN SWITCH 2034

COMBINER 2036

2030

DATA

DATA+BACKUP POWER

DATA+POWER

DATA ONLY

SPARE PAIR NO DATA NO POWER

DATA+POWER

DATA+POWER

DATA+BACKUP POWER

DATA+POWER

DATA+BACKUP POWER

FIG. 10B

MANAGEMENT STATION

2090

2072

2070

LAN/WAN

2088

HUB

POWER MANAGEMENT & CONTROL UNIT

2060

2082

POWER SUPPLY

2084

LAN SWITCH

POWER SUPPLY INTERFACE

2080

2086

DATA

DATA+BACKUP POWER

DATA+POWER

SPARE PAIR

POWER

DATA

DATA

2068

DATA+BACKUP POWER

2066

DATA+BACKUP POWER

2062

DATA+POWER

HUB CAMERA

2064

FIG. 11A

MANAGEMENT
WORK STATION

HUB 2100

LAN SWITCH

POWER MANAGEMENT & CONTROL UNIT

POWER SUPPLY 2132

COMBINER

LAN/WAN

2133

2130
2136

2134

2140

2142

DATA+BACKUP POWER

SEP

2112

DATA+POWER

SEP 2144

HUB CAMERA 2114

2146 SEP

2116

DATA+BACKUP POWER

DATA+POWER

DATA+POWER

DATA+POWER

DATA+POWER

SPARE PAIR

POWER

DATA+BACKUP POWER

DATA+BACKUP POWER

2148 SEP

2118

2150 SEP

2120

2122

DATA

FIG. 11B

MANGMENT WORK STATION

2190

LAN/WAN

HUB

2150

LAN SWITCH

POWER MANGMENT & CONTROL UNIT

2183

POWER SUPPLY

2182

POWER SUPPLY INTERFACE

2180

2186

2184

DATA+BACKUP POWER

CON 2192

2162

DATA+POWER

CON 2194

HUB CAMERA

2164

DATA+BACKUP POWER

CON 2196

2166

DATA+POWER

DATA+BACKUP POWER

POWER

SPARE PAIR

DATA

DATA

CON 2198

2168

DATA

2172

2170

CON 2199

FIG. 12A

TO
MANAGEMENT
STATION

2168

COMMUNICATION

2038

2164

2162

MICROPROCESSOR

MEMORY

2166

BUS

SPARC
CONTROLLERS

2160

2036

DC BUS

SPEAR

SPEAR

SPEAR

SPEAR

SPEAR

2224

POWER
SUPPLY

2032

2010

LAN SWITCH

2034

COUPLERS &
FILTERS

2037

POWER+DATA

FIG. 12B

FIG. 13A

TO MANAGMENT STATION

2130

COMMUNICATION 2368

MICROPROCESSOR 2364   2133

MEMORY 2366

BUS 2362

SPARC CONTROLLERS 2360

SPEAR

SPEAR

SPEAR

SPEAR

SPEAR 2324

2136

DC BUS

POWER SUPPLY 2132

LAN SWITCH 2134

2100

COUPLERS & FILTER 2137

POWER+DATA

FIG. 13B

TO
MANAGMENT
STATION

2180

2384 — COMMUNICATION

2183 — MICROPROCESSOR

2380

MEMORY

2382

2378 — BUS

2376 — SPARC CONTROLLERS

2386

DC BUS

SPEAR

SPEAR

SPEAR

SPEAR

SPEAR — 2374

POWER SUPPLY — 2182

2150

2184 — LAN SWITCH

FILTERS

2187

POWER   DATA

LAN DATA
FROM SEPARATOR/CONNECTOR

FIG. 14A

LAN POWER
IN

SENSOR ⌒2416

2400

2404

ESSENTIAL CIRCUITRY

POWER
SUPPLY

SW

NON ESSENTIAL CIRCUITRY

2402

2406

2410

CONTROLLER

2414

MAINS

POWER
SUPPLY

2412

FIG. 14B

LAN POWER
IN

SENSOR ⌒2446

2440

SW

NODE CIRCUITRY

2438

POWER
SUPPLY

MONITORING CIRCUITRY

2436

2448

CONTROLLER

2444

MAINS

POWER
SUPPLY

2442

FIG. 15

FIG. 16

SUPPLY POWER TO AT LEAST SOME NODES
VIA COMMUNICATION CABLING

MONITOR + CONTROL

INVOLUNTARY POWER
MANAGEMENT

FIG. 19A–D, 20A–D

VOLUNTARY POWER
MANAGEMENT

SLEEP MODE OPTION	PRIORITIZATION OPTION
FIG. 21A–D, 22A–D	FIG. 23A–D, 24A–D

FIG. 17

INITIALIZE THE POWER HUB

DETERMINE NODE
TYPE FOR NODE #1

IF THE NODE IS DETERMINED
AS POL LOAD AND LINE N IS
ENABLED TO BE OPERATED
ACCORDING TO INTERNAL TABLE

THEN-SET SPEAR PARAMETERS
ACCORDING TO INTERNAL
TABLE DEFINITIONS

WHEN APPLICABLE-SEND PREDETERMINED
SIGNALING TO REMOTE LOAD

REPORT LINE STATUS TO THE
MANAGEMENT STATION

INCREMENT N

FIG. 18A

IS LINE N SET TO BE ACTIVE ? —NO→ RETURN

↓ YES

MEASURE VOLTAGE AT SPEAR OUTPUT

↓

$|V| > V_1$ —YES→ MARK LINE AS EXTERNAL VOLTAGE FEED

↓ NO

SET SPARC
$Vout = V_2$
$I_0 = I_{L1}$
SET SWITCH TO ON

↓

MEASURE Vout, I_0
AT 3 TIMES T_1, T_2, T_3
CLASSIFY LINE TYPE AS PER FOLLOWING

FIG. 18B

```
┌─────────────────────────┐        ┌─────────────────┐
│ Vout>V₂ and |Io|<I₂     │───────→│ REPORT:         │──────────┐
│ for all T₁, T₂ ,T₃      │        │ NO "LOAD"       │          │
└─────────────────────────┘        │ STATUS          │          │
                                   └─────────────────┘          │
                                                                │
┌─────────────────────────┐        ┌─────────────────┐          │
│ Vout<V₃ and Io>I₃       │───────→│ REPORT:         │─────────→│
│ for all T₁, T₂ ,T₃      │        │ "SHORT CIRCUIT" │          │
└─────────────────────────┘        │ STATUS          │          │
                                   └─────────────────┘          │
                                                                │
┌─────────────────────────┐        ┌─────────────────┐          │
│ Vout T₃ <V₄ and |IoT₁|< │───────→│ REPORT:         │─────────→│
│ |IoT₂ |<|IoT₃ |         │        │ "NIC LOAD"      │          │
└─────────────────────────┘        │ STATUS          │          │
                                   └─────────────────┘          │
                                                                │
┌─────────────────────────┐        ┌─────────────────┐          │
│ VoutT₁ >V₅ and Vout T₂> │───────→│ REPORT:         │─────────→│
│ V₅ and Vout T₃>V₅ and   │        │ "POL LOAD"      │          │
│ (IoT₁ >I₅ or  IoT₂ >I₅  │        │ STATUS          │          │
│   or IoT₃ >I₅ )         │        └─────────────────┘          │
└─────────────────────────┘                                     │
                                                                ▼
                                                        ┌───────────┐
                                                        │  SET      │
                                                        │  SWITCH   │
                                                        │  OFF      │
                                                        └───────────┘
                                                              │
                                                              ▼
                                                        (  RETURN  )
```

- $Vout > V_2$ and $|Io| < I_2$ for all T_1, T_2, T_3 → REPORT: NO "LOAD" STATUS
- $Vout < V_3$ and $Io > I_3$ for all T_1, T_2, T_3 → REPORT: "SHORT CIRCUIT" STATUS
- $Vout\ T_3 < V_4$ and $|IoT_1| < |IoT_2| < |IoT_3|$ → REPORT: "NIC LOAD" STATUS
- $VoutT_1 > V_5$ and $Vout\ T_2 > V_5$ and $Vout\ T_3 > V_5$ and ($IoT_1 > I_5$ or $IoT_2 > I_5$ or $IoT_3 > I_5$) → REPORT: "POL LOAD" STATUS

INVOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR NO FUNCTIONALITY

(A)

DETERMINE CURRENT TOTAL POWER
AVAILABILITY(TPA) AND CURRENT TOTAL
POWER CONSUMPTION (TPC)

(C)

SUPPLY POWER TO
ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B)

$\dfrac{TPC}{TPA}$?

> 0.95

(D)

DISCONNECT POWER
FROM NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geq$ 0.8
$\leq$ 0.95

(E)

DOES
ADDITIONAL NODE
REQUIRE POWER
?

NO

YES

(F)

IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING POWER
?

NO

YES

(G)

DISCONNECT LOWER PRIORITY
NODE FROM POWER

(H)

CONNECT HIGHER PRIORITY
NODE FROM POWER

FIG. 19A

INVOLUNTARY POWER MANAGEMENT, FULL
FUNCTIONALITY OR NO FUNCTIONALITY
EMERGENCY OVERRIDE

(J)

IS POWER
REQUIRED AT A NODE
ON EMERGENCY
BASIS ?

NO

YES

(K)

ASSIGN HIGHEST PRIORITY
TO NODE REQUIRING POWER
ON EMERGENCY BASIS

(L)

PROCEED ACCORDING TO
STEPS (A–H) OF FIG. 19A

(M)

IS
EMERGENCY SITUATION
TERMINATED?

NO

YES

(N)

REDUCE PRIORITY OF
NODE TO ITS USUAL PRIORITY

FIG. 19B

INVOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR NO FUNCTIONALITY
QUEUE CONTROLLRD PRIORITY

(A)

DETERMINE CURRENT TOTAL POWER
AVAILABILITY(TPA) AND CURRENT TOTAL
POWER CONSUMPTION (TPC)

(C)

SUPPLY POWER TO
ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B)

$\dfrac{TPC}{TPA}$?

> 0.95

(D)

DISCONNECT POWER
FROM NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geqslant 0.8$
$\leqslant 0.95$

(E)

DOES
ADDITIONAL NODE
REQUIRE POWER
?

NO

YES   (I)

ADD NODE TO BOTTOM OF QUEUE

FIG. 1.9C

INVOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR NO FUNCTIONALITY
TIME SHARING

(A)

DETERMINE CURRENT TOTAL POWER
AVAILABILITY(TPA) AND CURRENT TOTAL
POWER CONSUMPTION (TPC)

(C)

SUPPLY POWER TO
ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

(B)

< 0.8 $\frac{TPC}{TPA}$?   > 0.95

$\geqslant 0.8$
$\leqslant 0.95$

(D)

DISCONNECT POWER
FROM NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

(E)

DOES
ADDITIONAL NODE
REQUIRE POWER
?

NO

YES

(F)

IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING POWER
?

NO

YES

(G)

DISCONNECT LOWER PRIORITY
NODE FROM POWER

(H)

CONNECT HIGHER PRIORITY
NODE FROM POWER

FIG. 19D

INVOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR REDUCED FUNCTIONALITY

(A')

DETERMINE CURRENT TOTAL POWER
AVAILABILITY (TPA) AND CURRENT TOTAL
POWER CONSUMPTION (TPC)

(C')

SUPPLY FULL POWER
TO ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B')

$\dfrac{TPC}{TPA}$?

> 0.95

(D')

REDUCE POWER
TO NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geqslant$ 0.8
$\leqslant$ 0.95

(E')

DOES
ADDITIONAL NODE
REQUIRE ADDITIONAL
POWER ?

NO

YES

(F')

IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING ADDITIONAL
POWER ?

NO

YES

(G')

REDUCE POWER TO LOWER
PRIORITY NODE

(H')

PROVIDE ADDITIONAL POWER
TO HIGHER PRIORITY NODE

FIG. 20A

INVOLUNTARY POWER MANAGEMENT, FULL
FUNCTIONALITY OR REDUCED   FUNCTIONALITY, EMERGENCY OVERRIDE

(J')

IS ADDITIONAL
POWER REQUIRED AT A NODE
ON EMERGENCY
BASIS ?

NO

YES

(K)

ASSIGN HIGHEST PRIORITY
TO NODE REQUIRING POWER
ON EMERGENCY BASIS

(L')

PROCEED ACCORDING TO
STEPS (A'-H') OF FIG. 20A

(M)

IS
EMERGENCY. SITUATION
TERMINATED?

YES

(N)

REDUCE PRIORITY OF
NODE TO ITS USUAL PRIORITY

FIG. 20B

INVOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR REDUCED FUNCTIONALITY
QUEUE CONTROLLRD PRIORITY

(A)

DETERMINE CURRENT TOTAL POWER
AVAILABILITY(TPA) AND CURRENT TOTAL
POWER CONSUMPTION (TPC)

(C')

SUPPLY FULL POWER TO
ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

(B)

< 0.8 $\dfrac{TPC}{TPA}$? > 0.95

(D')

REDUCE POWER
TO NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geqslant 0.8$
$\leqslant 0.95$

(E')

DOES
ADDITIONAL NODE
REQUIRE ADDITIONAL
POWER
?

NO

YES   (I)

ADD NODE TO BOTTOM OF QUEUE

FIG. 20C

INVOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR REDUCED FUNCTIONALITY
TIME SHARING

(A)

DETERMINE CURRENT TOTAL POWER
AVAILABILITY(TPA) AND CURRENT TOTAL
POWER CONSUMPTION (TPC)

(C')

SUPPLY FULL POWER
TO ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B)

$$\frac{TPC}{TPA} \, ?$$

> 0.95

(D')

REDUCE POWER
TO NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geqslant 0.8$
$\leqslant 0.95$

(E')

DOES
ADDITIONAL NODE
REQUIRE ADDITIONAL
POWER ?

NO

YES

(F')

IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING ADDITIONAL
POWER ?

NO

YES

(G')

REDUCE POWER TO LOWER
PRIORITY NODE

(H')

PROVIDE ADDITIONAL POWER
TO HIGHER PRIORITY NODE

FIG. 20D

DETERMINE TIME DURATION TD1
SINCE LAST ACTIVITY OF NODE

FIG. 21A

NO

IS TD1 > THRESHOLD
?

YES

YES

WAS USER OR
SYSTEM CONTRAINDICATION
RECEIVED ?

NO

OPERATE IN
SLEEP MODE

DETERMINE TIME DURATION TD2
SINCE LAST COMMUNICATION

FIG. 21B

NO

IS TD2 > THRESHOLD
?

YES

YES

WAS USER OR
SYSTEM CONTRAINDICATION
RECEIVED ?

NO

OPERATE IN
SLEEP MODE

FIG. 21C

```
┌──────────────────────────────────┐
│                                  ▼
│        ┌─────────────────────────────────┐
│        │   DURING TIME DURATION TD3      │
│        │ OPERATE NODE WITH FULL POWER    │
│        └─────────────────────────────────┘
│                      │
│                      ▼
│        ┌─────────────────────────────────┐
│        │   DURING TIME DURATION TD4      │
│        │  OPERATE NODE IN SLEEP MODE     │
│        └─────────────────────────────────┘
│                      │
└──────────────────────┘
```

FIG. 21D

```
        ┌──────────────────────────────────┐
        │                                  │
        ▼                                  │
┌──────────────┐        ┌────────────────────────────┐
│   OPERATE    │        │     PERFORM SELF TEST       │
│   NORMALLY   │        └────────────────────────────┘
└──────────────┘                     │
        ▲                            ▼
        │                       ╱─────────╲
        │  PASS                ╱           ╲
        └─────────────────────│  PASS/FALL  │
                               ╲           ╱
                                ╲─────────╱
                                     │ FAIL
                                     ▼
                        ┌────────────────────────────┐
                        │   OPERATE IN SLEEP MODE     │
                        └────────────────────────────┘
```

FIG. 22A

DETERMINE TIME DURATION TD11 SINCE LAST ACTIVITY OF NODE SENSED BY HUB

IS TD11 > THRESHOLD ?

NO

WAS USER OR SYSTEM CONTRAINDICATION RECEIVED ?

YES

YES

NO

OPERATE IN SLEEP MODE

FIG. 22B

DETERMINE TIME DURATION TD12 SINCE LAST COMMUNICATION SENSED BY HUB

IS TD12 > THRESHOLD ?

NO

WAS USER OR SYSTEM CONTRAINDICATION RECEIVED ?

YES

YES

NO

OPERATE IN SLEEP MODE

FIG. 22C

DURING TIME DURATION TD13 DETERMINED
BY CLOCK AT THE HUB
OPERATE NODE WITH FULL POWER

DURING TIME DURATION TD14 DETERMINED
BY CLOCK AT THE HUB
OPERATE NODE IN SLEEP MODE

FIG. 22D

OPERATE
NORMALLY

HUB PERFORM TEST OF THE NODE

PASS

PASS/FALL

FAIL

OPERATE NODE IN SLEEP MODE

VOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR NO FUNCTIONALITY

(A)

DETERMINE CURRENT TOTAL POWER
AVAILABILITY(TPA) AND CURRENT TOTAL
POWER ALLOCATION (TPL)

(C)

SUPPLY POWER TO
ADDITIONAL NODES,
ONE—BY—ONE ON
A PRIORITIZED BASIS

(B)

< 0.8 $\dfrac{TPC}{TPL}$? > 0.95

(D)

DISCONNECT POWER
FROM NODES
ONE—BY—ONE ON
A PRIORITIZED BASIS

≥ 0.8
≤ 0.95

(E)

DOES
ADDITIONAL NODE
REQUIRE POWER
?

NO

YES

(F)

IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING POWER
?

NO

YES   (G)

DISCONNECT LOWER PRIORITY
NODE FROM POWER

(H)

CONNECT HIGHER PRIORITY
NODE FROM POWER

FIG. 23A

VOLUNTARY POWER MANAGEMENT, FULL
FUNCTIONALITY OR NO FUNCTIONALITY
EMERGENCY OVERRIDE

```
                                    (J)
         NO          ◇ IS POWER
      ◄──────────────  REQUIRED AT A NODE
                       ON EMERGENCY
                       BASIS ?

                         │ YES        (K)
                         ▼
                  ┌──────────────────────┐
                  │ ASSIGN HIGHEST PRIORITY │
                  │ TO NODE REQUIRING POWER │
                  │ ON EMERGENCY BASIS      │
                  └──────────────────────┘

                         │              (L)
                         ▼
                  ┌──────────────────────┐
                  │ PROCEED ACCORDING TO   │
                  │ STEPS (A-H) OF FIG. 19A │
                  └──────────────────────┘

                         │
                         ▼
                                    (M)
         NO          ◇ IS
      ◄──────────────  EMERGENCY SITUATION
                       TERMINATED?

                         │ YES        (N)
                         ▼
                  ┌──────────────────────┐
                  │ REDUCE PRIORITY OF     │
                  │ NODE TO ITS USUAL PRIORITY │
                  └──────────────────────┘
```

FIG. 23B

VOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR NO FUNCTIONALITY
QUEUE CONTROLLED PRIORITY

(A)
DETERMINE CURRENT TOTAL POWER
CONSOMPTION (TPC) AND CURRENT TOTAL
POWER ALLOCATION (TPL)

(C)
SUPPLY POWER TO
ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B)
$\dfrac{TPC}{TPL}$?

> 0.95

(D)
DISCONNECT POWER
FROM NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geqslant$ 0.8
$\leqslant$ 0.95

(E)
DOES
ADDITIONAL NODE
REQUIRE POWER
?

NO

YES   (I)

ADD NODE TO BOTTOM OF QUEUE

FIG. 23C

VOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR NO FUNCTIONALITY
TIME SHARING

(A)

DETERMINE CURRENT TOTAL POWER
AVAILABILITY(TPA) AND CURRENT TOTAL
POWER ALLOCATION (TPL)

(C)

SUPPLY POWER TO
ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B)

$$\frac{TPC}{TPL} \ ?$$

> 0.95

(D)

DISCONNECT POWER
FROM NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geqslant 0.8$
$\leqslant 0.95$

(E)

DOES
ADDITIONAL NODE
REQUIRE POWER
?

NO

YES

(F)

IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING POWER
?

NO

YES

(G)

DISCONNECT LOWER PRIORITY
NODE FROM POWER

(H)

CONNECT HIGHER PRIORITY
NODE FROM POWER

FIG. 23D

VOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR REDUCED FUNCTIONALITY

(A')
DETERMINE CURRENT TOTAL POWER
CONSUMPTION (TPC) AND CURRENT TOTAL
POWER ALLOCATION (TPL)

(C')
SUPPLY FULL POWER
TO ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B')
$\dfrac{TPC}{TPL}$?

> 0.95

(D')
REDUCE POWER
OF NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

$\geqslant$ 0.8
$\leqslant$ 0.95

(E')
DOES
ADDITIONAL NODE
REQUIRE ADDITIONAL
POWER ?

NO

YES

(F')
IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING ADDITIONAL
POWER ?

NO

YES

(G')
REDUCE POWER TO LOWER
PRIORITY NODE

(H')
PROVIDE ADDITIONAL POWER
TO HIGHER PRIORITY NODE

FIG. 24A

VOLUNTARY POWER MANAGEMENT, FULL
FUNCTIONALITY OR REDUCED FUNCTIONALTY, EMERGENCY OVERRIDE

FIG. 24B

VOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR REDUCED FUNCTIONALITY
QUEUE CONTROLLED PRIORITY

FIG. 24C

VOLUNTARY POWER MANAGEMENT FULL
FUNCTIONALITY OR REDUCED FUNCTIONALITY
TIME SHARING

(A)
DETERMINE CURRENT TOTAL POWER
CONSUMPTION (TPC) AND CURRENT TOTAL
POWER ALLOCATION (TPL)

(C')
SUPPLY FULL POWER
TO ADDITIONAL NODES,
ONE-BY-ONE ON
A PRIORITIZED BASIS

< 0.8

(B)
$\frac{TPC}{TPL}$?

> 0.95

(D')
REDUCE POWER
TO NODES
ONE-BY-ONE ON
A PRIORITIZED BASIS

≥ 0.8
≤ 0.95

(E')
DOES
ADDITIONAL NODE
REQUIRE ADDITIONAL
POWER ?

NO

YES

(F')
IS A
LOWER PRIORITY
NODE CURRENTLY
CONSUMING ADDITIONAL
POWER ?

NO

YES

(G')
REDUCE POWER TO LOWER
PRIORITY NODE

(H')
PROVIDE ADDITIONAL POWER
TO HIGHER PRIORITY NODE

FIG. 24D